



DIMAPCHEM-EP MU HS

**SOLVENTED HIGH BUILD HIGH SOLID MULTI USE
PRIMER & FINISH COATING FOR STEEL & CONCRETE SURFACES**

BENEFITS

- Can be used on steel, galvanized steel and concrete substrates & has excellent adhesion.
- Excellent protective properties.
- Excellent over coating characteristics.
- Low VOC.
- Flexible.
- Chemical resistant. **PRODUCT**

m²/lit : ~10m²/lit @ 90mic

DIMAPCHEM

APPLICATION

Surface Preparation: Steel & Concrete Surfaces: Oil contaminated surfaces should be thoroughly cleaned with a degreaser and sand blasted. Where this is not possible, minimal surface preparation of wire brushing should be done.

DIMAPCHEM-EP (MU HS) can be applied directly to steel & concrete surfaces.

Priming: Normally primer is not required. But after grit blasting / sand blasting, if there is any delay to erection, one coat of **DIMAPCHEM-EP (MU) up 60% with VERLASOL EP** is advisable to prevent further flush rust.

Mixing: **DIMAPCHEM-EP (MU HS)** is supplied as ready to use in pre-weighed packs of resin and hardener for easy on site mixing. Pour the hardener into the resin can, mix well using a paddle attached to an electric drill, for 2-3 minutes until a uniform color is obtained.

DEKWANEH-ROUND POINT
AL HAYEK -38 CENTRE
HAYEK – 1RST FLOOR
+961 : 71-609609 7 -949396
WWW.DIMAPCHEM.COM



DIMAPCHEM SARL-FANAR-RWEISS –LEBANON - web :www.DIMAPCHEMlb.com-E mail :infotec@DIMAPCHEMlb.com -telfax:+9615454292

Application: DIMAPCHEM-EP (MU HS) may be applied by brush or airless spray to give a continuous coating on the prepared surface. A second coat may be subsequently applied when first coat is dried. Preferably next day.

Cleaning: Tools and mixers should be cleaned with **DIMAPCHEM-solvent** / Tool cleaner immediatel after use.

PACKING & COVERAGE

DIMAPCHEM-EP (MU HS) is supplied in U.S Gallon and Pail pack.

SHELF LIFE & STORAGE

DIMAPCHEM-EP (MU HS) will have a shelf life of **12 months** in unopened containers when kept in dry conditions at a temperature between 5°C to 45°C. Storage at higher temperature or high humidity may reduce shelf life.

HEALTH & SAFETY

Hand Gloves must be used. Goggles for overhead application to prevent contact with eye. Any splashes on skin should be washed with water and medical advice sought. In enclosed areas, good ventilation must be ensured, and smoking must be strictly prohibited while using **DIMAPCHEM-EP (MU HS)**.

SPECIFICATION

DIMAPCHEM-EP (MU HS) is a two pack, high build, solvented, epoxy coating for steel structures to provide protection from weathering and abrasion. One liter will cover an area of approximately 6-7 sq.mt. For recommended two coats, in accordance with the instruction of DIMAPCHEM- DIMAPCHEM sarl

QUALITY ASSURANCE

DIMAPCHEM sarl manufactures entire range of construction chemicals Protective coatings , wood coatings ,decorative paints, water proofing systems.

DEKWANEH-ROUND POINT
AL HAYEK -38 CENTRE
HAYEK – 1RST FLOOR
+961 : 71-609609 7 -949396
WWW.DIMAPCHEM.COM



TECHNICAL SERVICES

While new advances and changes will take place but one thing will never change is quality and meeting special needs of our customers. Our technical personnel & experts are available to provide additional information and technical assistance. We are eager to work with you in development of new product and resolve your problem.

DIMAPCHEM

The information given in this data sheet is based on both the current development work and many years of field experience. Whilst every effort is made to ensure that the information is reliable, we cannot accept the responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. In view of the continuing research and development being undertaken in our laboratories we advise customers in their-own interest to ensure that this data sheet has not been superseded by more up-to-date publication. All products are sold subjected to our standard conditions of sale which are available on request. Field services, where provided, does not constitute supervisory responsibility. For additional information, please contact our local DIMAPCHEM SARL – DIMAPCHEM-representative.

®Registered Trade Mark

DEKWANEH-ROUND POINT
AL HAYEK -38 CENTRE
HAYEK – 1ST FLOOR
+961 : 71-609609 7 -949396
WWW.DIMAPCHEM.COM



Technical Summary For SAFECORE EP MU HS	
Chemistry	
<i>Color</i>	White, Grey & (Special colors on order)
<i>gloss level</i>	Semi Gloss
<i>Volume Solids</i>	85% ± 2%
<i>typical thickness</i>	85 Micron dry Equivalent to 100 Microns Wet.
<i>theoretical coverage</i>	25 M2 / U.S Gallon at 150 Microns
<i>practical coverage</i>	Allow Appropriate Loss Factor
<i>Flash Point</i>	27 °C
<i>Specific Gravity</i>	1.5 Kg/l
<i>Thinner to use</i>	VERLASOL EP
Application Method	
<i>common application fields</i>	General Steel & Concrete
<i>Application methods</i>	Airless/tip: .018"/.020", pressure at tip not less than 150 bar Conventional / (pressure pot): 1.4mm Nozzle / 4 Bars Brush Roller
<i>Number of Coats</i>	Two Coats
<i>Recommended time interval between coats at 21 °C</i>	3 Hours
<i>Thinning</i>	
<i>HARDENER</i>	20% HARDENER EP HS
<i>cleaner</i>	DIMAPCHEM Cleaning Thinner

DEKWANEH-ROUND POINT
AL HAYEK -38 CENTRE
HAYEK – 1RST FLOOR
+961 : 71-609609 7 -949396
WWW.DIMAPCHEM.COM



<i>preparation of substrate</i>	Mechanically or abrasive blasting /SAFECORE ZRP, ZRP HZ
<i>Dry Time</i>	1.5 Hour Touch Dry, 3 - 5 Hours Hard
<i>Time to clean application equipment</i>	Immediately after use.
<i>Packaging</i>	1 Quart, U.S. Gallon & U.S.Pail
<i>storage</i>	Between 5C and 45C Degrees
<i>Shelve life storage</i>	12 Month
<i>Shipping weight not including pallets and boxes</i>	us gallon/---kg imp gallon/---kg pail of 5usg /---kg pail 25litrs----kg
	<i>recommended systems and compatibility</i>
Top Coat For	SAFECORE ZRP, ZRP HZ
Top Coat	SAFECORE PU - UD, SD, D

DEKWANEH-ROUND POINT
AL HAYEK -38 CENTRE
HAYEK – 1RST FLOOR
+961 : 71-609609 7 -949396
WWW.DIMAPCHEM.COM