



TM

VERLASIL W

ACTIVE COMPONENT WATER BASE PENETRATING WATER REPELLENT

BENEFITS

- Easily applied VERLASIL W treatment giving a self cleaning, hydrophobic surface to masonry, brick, stone, concrete, mortar and asbestos sheeting.
- Excellent repellent
- Increases free-flow resistance and minimizes efflorescence.
- Penetrates into substrates.
- Excellent performance and stability.
- Chemical resistance.

USES

WATERREPELL SUPER is used to protect exposed reinforced concrete structures & other cementitious substrates & masonry. Suitable for use on mineral substrates such as brick, stone, concrete, mortar and asbestos sheeting.

DESCRIPTION

WATERREPELL SUPER is supplied as ready to use, single component penetrating silane-siloxane system which penetrates into porous substrates and then reacts to produce a bonded hydrophobic lining to the pores. It significantly reduces absorption of water into the substrate. **WATERREPELL SUPER** prolongs the clean appearance of buildings, reduces chemical attack, minimizes efflorescence. Any other common water repellent will penetrate and provide water repellence by chemically reacting with the substrate. Due to the excellent water repel properties dirt and other atmospheric impurities are washed off by rain and its clean appearance is maintained for a longer period.

APPLICATION

Surface Preparation : All surfaces should be dry and free from contamination such as oil, grease, loose particles, laitance & all traces of mould & loose oils.

Application : **WATERREPELL SUPER** should be applied in coats dry using portable spray equipment.

Cleaning : All tools and equipment should be washed immediately after use.

DEKWANEH-ROUND POINT
AL HAYEK -38 CENTRE
HAYEK – 1ST FLOOR
+961 : 71-609609 7 -949396
WWW.DIMAPCHEM.COM



SHELF LIFE&STORAGE

WATERREPELL SUPER will have a shelf life of **12 months** in unopened containers when kept in dry conditions at a temperature between 5°C to 45°C. Storage at higher temperature or high humidity may reduces helf life.

PACKING &COVERAGE

WATERREPELL SUPER is available in 1,15, 10, 50 & 100 Ltrs. carboys. 1 ltr. **WATERREPELL SUPER** will cover approx.4to5m²ofsurface.

HEALTH &SAFETY

WATERREPELL SUPER is splashes on skin when occurs should be washed with water. **WATERREPELL SUPER** when comes in contact with acids, bases, amines and heavy metals or there compounds, the rate of hydrogen evolution increases. Do not store material in the presence of these contaminants, as hydrogen evolution will occur. Do not store or use near sparks or open flames. Do not smoke in the vicinity of application. Use this material in a well ventilated area away from sparks and open flames

- Appearance : Clear Free flow in liquid
- Color : Water white to pale yellow
- Non Volatile matter, % : 3.5–5.0
- Specific gravity
@30°C,gms/ml : 0.80+0.02
- Application : Spray or brush
- Surfaced rtime, minutes : 20-25

TECHNICALSERVICES

While new advances and changes will take place but one thing will never change is quality and meeting special needs of our customers. Our technical personnel & experts are available to provide additional information and technical assistance. We are eager to work with you in development of new product and resolve your problem.

DEKWANEH-ROUND POINT
AL HAYEK -38 CENTRE
HAYEK – 1RST FLOOR
+961 : 71-609609 7 -949396
WWW.DIMAPCHEM.COM