


Visit us on: http://www.dimapchem.com/


EMAIL: Info@dimapchem.com

ALL PRODUCTS EXAMINED BY GFC LAB-ITALY

CEMENT PAINT

Product Description:





- **Precautions:** Wear gloves and eye protection, ensure good ventilation, and avoid skin and inhalation contact.
- Storage: Store in a cool, dry place, away from sunlight and children.

Quality & Durability:

Resistant to water penetration and dampness

Anti-fungal and anti-algae properties UV-resistant to prevent fading and chalking

Long-lasting, ensuring 5+ years of durability under normal conditions Breathable finish prevents trapped moisture

APPLICATION INSTRUCTIONS

Surface Preparation

- 1. Ensure the surface is clean, dry, and free from dust, dirt, grease, or loose particles.
- 2. Remove old flaking paint, algae, or fungi using a wire brush and suitable cleaning agents.
- 3. Dampen the surface with clean water before application to enhance adhesion.

Application

- 1. Apply using a brush, roller, or spray in two coats.
- 2. Ensure a 4-6 hour drying time between coats.
- 3. Keep the surface damp for at least 24 hours after application for enhanced durability.

Technical Details

- **Composition:** High-quality Portland cement, pigments, and waterproofing agents
- Color: cement
- Drying Time: Touch dry in 30-45 minutes, complete drying in 24 hours
- Coverage: 16 meters per gallon, depending on surface porosity
- Water Resistance: Excellent after full curing



Uses:

- Exterior and interior walls
- Residential and commercial buildings
- Concrete, plastered, and brick surfaces
- Boundary walls and fences
- Sloped roofs and parapet walls
- Basements and damp-prone areas