

Visit us on: <a href="http://www.dimapchem.com/">http://www.dimapchem.com/</a>

EMAIL: Info@dimapchem.com

**ALL PRODUCTS EXAMINED BY GFC LAB-ITALY** 

## LATEX EMULSION SATIN MATT



# **Product Description:**

Latex Emulsion Satin Matt is a high-quality rich in titan and pure acrylic in italy raw paint that offers a smooth, matte finish for both interior and exterior applications. This versatile emulsion paint is formulated to provide excellent coverage and a durable, long-lasting finish, making it ideal for use on walls and ceilings in both residential and commercial spaces. Its low-sheen matte finish helps to hide imperfections and stains while providing a sophisticated, modern look. With excellent adhesion and easy application, Latex Emulsion Matt is a go-to solution for various painting projects. 300 wash



# **Health and Safety:**

- **Precautions:** Wear gloves and eye protection, ensure good ventilation, and avoid skin and inhalation contact.
- Storage: Store in a cool, dry place, away from sunlight and children.



# **Quality & Durability:**

### **Durability:**

Known for its long-lasting durability, Semi Latex offers excellent resistance to dirt, stains, and environmental pollutants. Its semi-gloss finish enhances surface protection, providing better resistance to moisture, wear, and mildew.

#### Resistance:

Offers superior resistance to cracking, peeling, fading, and yellowing, making it suitable for high-traffic areas and variable environmental conditions.

# APPLICATION INSTRUCTIONS



Mixing:

Stir the paint thoroughly before use to ensure consistency and even distribution of pigments.

Application Tools:

Apply with a high-quality brush, roller, or spray gun. For larger areas, rollers are preferred for quicker and more uniform coverage.

### **Technical Details**

• Type: rich in titan and pure acrylic

• Finish: Matt (non-reflective finish)

• Color Availability: Wide range of colors (custom shades available upon request)

• **Density:** 1.2 - 1.4 g/cm<sup>3</sup>

• Viscosity: 90 - 110 KU

• Coverage: Approximately 45 -60 m² per gallon per coat

During

• **Drying Time:** 30 minutes (touch-dry); 2-3 hours for re-coating

**VOC Content:**  $\leq 50 \text{ g/L}$ 

• Thinner: Water (if necessary)

• Shelf Life: 12 months when stored in a cool, dry

place in sealed containers

## Uses:

## • Interior Applications:

Ideal for use on walls and ceilings in living rooms, bedrooms, hallways, kitchens, and bathrooms. The matte finish helps in hiding surface imperfections and provides a smooth, uniform look.

### • Exterior Applications:

Suitable for outdoor use on masonry, concrete, and primed wood surfaces, offering good resistance to weathering and fading in mild outdoor conditions.