

Visit us on: http://www.dimapchem.com/

EMAIL: Info@dimapchem.com

ALL PRODUCTS EXAMINED BY GFC LAB-ITALY

## SEMI LATEX EMULSION



## **Product Description:**

Semi Latex is a high-performance water-based coating designed for a wide range of applications. This versatile product provides a smooth, durable finish, combining the benefits of latex with semigloss characteristics for an attractive and functional surface. Ideal for both interior and exterior surfaces, Semi Latex delivers a longlasting, easy-to-maintain finish with superior adhesion and coverage. Available in a wide range of colors, it enhances the aesthetic appeal while offering resistance to wear and environmental factors.



## **Health and Safety:**

- **Precautions:** Wear gloves and eye protection, ensure good ventilation, and avoid skin and inhalation contact.
- Storage: Store in a cool, dry place, away from sunlight and children.



# Quality & Durability:

#### **Durability:**

Known for its long-lasting durability, Semi Latex offers excellent resistance to dirt, stains, and environmental pollutants. Its semi-gloss finish enhances surface protection, providing better resistance to moisture, wear, and mildew.

#### Resistance:

Offers superior resistance to cracking, peeling, fading, and yellowing, making it suitable for high-traffic areas and variable environmental conditions.

# APPLICATION INSTRUCTIONS



Mixing:

Stir the Semi Latex thoroughly before use to ensure even consistency.

**Application Tools:** 

Use a brush, roller, or airless sprayer for application. For roller applications, use a high-quality microfiber or foam

### **Technical Details**

Type: Water-based semi-gloss paint

• Finish: Semi-gloss

Color Availability: Wide range of colors (custom colors available upon request)

**Density:** 1.3 - 1.5 g/cm<sup>3</sup>

Viscosity: 90 - 120 KU

Coverage: Approximately 35-50 m<sup>2</sup> per gallon per coat, depending on surface texture and porosity

**Drying Time:** 1-2 hours for touch-dry; 4-6 hours for re-coating

• **VOC Content:**  $\leq 50 \text{ g/L}$ 

• Thinner: Water (if necessary)

**Shelf Life:** 12 months in sealed containers

## Uses:

## **Interior Applications:**

ideal for use on walls, ceilings, doors, trim, and furniture in living rooms, bedrooms, kitchens, and bathrooms.

**Exterior Applications:** 

Suitable for exterior surfaces such as wood, metal, masonry, and concrete

Commercial & Residential Use:

Perfect for both residential and commercial spaces, including offices, schools, hospitals, and retail stores.